


## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING







5.00±0.10

$D \Lambda I$		<b>'D'</b>	ľ	ГΙ	ιт	-	
BAI	IVI I	PL	1//	H		FR.	

REV. 001	VALUE		
CENTER WAVELENGTH (CWL)	1550 ± 2nm		
FULL WIDTH HALF MAX (FWHM)	10 ± 2nm		
MINIMUM TRANSMISSION	≥85%		
BLOCKING	200 - 1800nm		
SURFACE QUALITY	80-50		
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING		
COATING TYPE	HARD COATED		
DURABILITY	MIL-C-48497A, SECT. 3.4.1		
ENVIRONMENTAL	MIL-STD-801F, SECT. 507.4		

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

			Edmund Optics®				
THIRD ANGLE PROJECTION		TITLE	OD4, Ø50mm, 1550nm x 10nm, HC, BP	FILTER			
ALL DIMS IN	mm	DWG NO	86094	SHEET 1 OF 1			