

1. SUBSTRATE MATERIAL: BOROFLOAT®/SUPREMAX®

2. PARABOLIC SURFACE:

Z=Y²/[4 * EFL]


3. COATING (APPLY ACROSS CLEAR APERTURE)


S1: PROTECTED GOLD R(avg) >96% @ 700 - 2000 R(avg) >96% @ 2000 - 10000nm S2: NONE

- 4. EDGES: MOLDED EDGE ACCEPTABLE
- 5. POWER, IRREGULARITY, SURFACE QUALITY AND COATING SPECIFICATIONS APPLY ACROSS CLEAR APERTURE



7. Rohs Compliant





SECTION C-C

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

| SHAPE | S1 CONCAVE | S2 PLANO | | | | |
|------------------------|----------------------|----------------------|----------------|----------------------------|---|--|
| EFFECIVE FOCAL LENGTH | 1524 | N/A | | Edmund Optics [®] | | |
| FOCAL LENGTH TOLERANCE | ±1.5% | N/A | | | 10" Diameter x 60" FL Protected Gold, Parabolic Mirror | |
| SURFACE QUALITY | 60-40 | FINE GRIND | THIRD ANGLE | TITLE | | |
| SURFACE FLATNESS | λ/8 | N/A | | | | |
| BEVEL | PROTECTIVE AS NEEDED | PROTECTIVE AS NEEDED | ALL DIMS IN mm | DWG NO | 32274566 SHE 1 OI | |

FOR INFORMATION ONLY:

PARTS TO THIS DRAWING

NUFACTURE