## NOTES:

1. SUBSTRATE MATERIAL: FUSED SILICA

2. COATING (APPLY ACROSS CLEAR APERTURE)

S1: NONE S2: NONE




ARROW POINTS TOWARDS TILTED SURFACE




FINE GROUND SURFACE

5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE

6. Rohs Compliant



ALL DIMS IN



## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

**S**1 **S2** REV. A **PLANO PLANO** SHAPE  $\infty$  $\infty$ **RADIUS** MIN CLEAR APERTURE Ø49.0 Ø49.0 20-10 20-10 SURFACE QUALITY λ/10 (OVER 25mm λ/10 (OVER 25mm SURFACE ACCURACY APERTURE) APERTURE) BEVEL PROTECTIVE AS NEEDED | PROTECTIVE AS NEEDED SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

34243

SHEET 1 OF 1

	B	<b>Edmund Optics</b> ®
THIRD ANGLE PROJECTION	TITLE	50mm FUSED SILICA WEDGED WINDOW

DWG NO