
NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) S1 & S2: RAVG ≤0.4% @ 425 - 675nm




5. Rohs Compliant

6. SURFACE FLATNESS (P-V): $\lambda/4$ (per inch over clear aperture)







PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2			
SHAPE	PLANO	PLANO			
SURFACE QUALITY	60-40	60-40			
CLEAR APERTURE	11.25 x 11.25	11.25 x 11.25 11.25 x 11.25			
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED			

			Edmund Optics®		
THIRD ANGLE PROJECTION	\$	TITLE	12.5mm SQ., 3mm THICK, VIS 0° COATE N-BK7 WINDOW	D λ/4	
ALL DIMS IN	mm	DWG NO	49628	SHEET 1 OF	

.E	12.5mm SQ., 3mm THICK, VIS 0° COAT N-BK7 WINDOW	ED λ/4
G NO	40700	SHEET

1 OF 1