
## NOTES:


1. SUBSTRATE: N-BK7


- 2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS)≤0.25% @ 880nm R(AVG) ≤1.25% @ 400 - 870nm R(AVG) ≤1.25% @ 890 - 1000nm

4. FINE GRIND SURFACE

5. Rohs Compliant







## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	S2			
SHAPE	PLANO	PLANO			
SURFACE QUALITY	60-40	60-40			
CLEAR APERTURE	67.50 x 67.50	67.50 x 67.50			
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED			
<u></u>					

			<b>Edmund Optics</b> ®		
	THIRD ANGLE PROJECTION		TITLE	75mm SQ., 4mm THICK, VIS-NIR COATED λ/4 N-BK7 WINDOW	
D	ALL DIMS IN	mm	DWG NO	37072	SHEET 1 OF 1