## NOTES:


1. SUBSTRATE: FUSED SILICA


2. RoHS: COMPLIANT

3. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN < 5 ARCMIN

4. COATING (APPLY ACROSS COATING APERTURE) S1& S2: R(AVG) ≤0.4% FROM 425 - 675nm

5. FINE GRIND SURFACE





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2				
SHAPE	PLANO	PLANO				
SURFACE ACCURACY	1λ	1λ		1		10mm DIA. VI
SURFACE QUALITY	60-40	60-40	THIRD ANGLE _ PROJECTION	$\bigoplus$	TITLE	TOMINI DIA. VI
CLEAR APERTURE	Ø9.00	Ø9.00	<u> </u>	I		
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	36968

	81	<b>Edmund Optics</b> ®
1	TITLE	10mm DIA. VIS 0°, 1λ FUSED SILICA WINDOW



SHEET 1 OF 1