NOTES:


1. SUBSTRATE: FUSED SILICA


2. RoHS: COMPLIANT

3. SURFACE S2 TO BE PARALLEL TO SURFACE \$1 TO WITHIN < 5 ARCMIN

4. COATING (APPLY ACROSS COATING APERTURE) S1& S2: R(AVG) ≤0.4% FROM 425 - 675nm

5. FINE GRIND SURFACE





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2]			B [®] Edmund Optic	C ®
SHAPE	PLANO	PLANO					,S
SURFACE ACCURACY	1λ	1λ				20mm DIA. VIS 0°, 1λ FUSED SILICA WIND)()\/
SURFACE QUALITY	60-40	60-40	THIRD ANGLE PROJECTION	TITLE		ZOMINI DIA. VIS O , TA FOSED SILICA WIND	OVV
CLEAR APERTURE	Ø18.00	Ø18.00					CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG	NO	36976	SHEET 1 OF 1

