



NOTES:

- 1. SUBSTRATE: CRYSTAL QUARTZ
- 2. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS) <0.25% @ 800nm DAMAGE THRESHOLD: 3.5 J/cm² @ 10ns @ 1064nm
- 3. SURFACE S1 TO BE PARALLEL TO SURFACE S2 TO WITHIN <0.5 arcsec
- 4. RETARDANCE: $\lambda/2\pm \lambda/200$
- 5. TRANSMITTED WAVEFRONT: λ/10 FOR CENTRAL 80% OF CLEAR APERTURE
- 6. Rohs Compliant









FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

GO ®	Edmund	Optics®
-------------	--------	---------

	\$1	\$2	THIRD ANGLE PROJECTION		TITLE	50.8mm DIA. 800nm λ/2 QUARTZ WAVEPLA ZERO ORDER	
CLEAR APERTURE	Ø34.0	Ø34.0		I			CLIEFT
SURFACE QUALITY	10-5	10-5	ALL DIMS IN	mm	DWG NO	85055	SHEET 1 OF 1