


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant












IR NEUTRAL DENSITY FILTER


REV. A	\$1	\$2]		P	Edmund Option	C®
SHAPE	PLANO	PLANO			W		
SURFACE QUALITY	60-40	60-40		1			
CLEAR APERTURE	Ø45	Ø45	THIRD ANGLE PROJECTION		TITLE	OD 0.3, Ø50mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A					CUEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	64358	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant












IR NEUTRAL DENSITY FILTER


REV. A	\$1	\$2				Edmund Optic)C®
SHAPE	PLANO	PLANO					,S
SURFACE QUALITY	60-40	60-40		1			
CLEAR APERTURE	Ø45	Ø45	THIRD ANGLE PROJECTION		TITLE	OD 0.5, Ø50mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A					CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	64359	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant












IR NEUTRAL DENSITY FILTER


REV. A	\$1	\$2]	P	Edmund Optic)C®
SHAPE	PLANO	PLANO				73
SURFACE QUALITY	60-40	60-40				
CLEAR APERTURE	Ø45	Ø45	THIRD ANGLE PROJECTION	TITLE	OD 1, Ø50mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A	'			CHEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	64360	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant












IR NEUTRAL DENSITY FILTER


REV. A	\$1	\$2]	P	Edmund Optics	C ®
SHAPE	PLANO	PLANO				5
SURFACE QUALITY	60-40	60-40				
CLEAR APERTURE	Ø45	Ø45	THIRD ANGLE PROJECTION	TITLE	OD 2, Ø50mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A				CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	64361	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant











IR NEUTRAL DENSITY FILTER

REV. A	\$1	\$2]	P	Edmund Optics	C ®
SHAPE	PLANO	PLANO				5
SURFACE QUALITY	60-40	60-40				
CLEAR APERTURE	Ø45	Ø45	THIRD ANGLE PROJECTION	TITLE	OD 3, Ø50mm, IR NEUTRAL DENSITY FILTE	
COATING APERTURE	Ø10.00	N/A				CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	64362	SHEET 1 OF 1